


X-50 High Precision Fiber Cleaver



Features

- ※ Small and light, easy to carry
- ※ Blade life more than 48000 times
- ※ Support cleaved length 5~16mm
- ※ High quality materials, stable performance
- ※ Apply to 250μm/ 900μm/ 3.0mm fibers
- ※ High precision, specially designed for splicing work

Specifications

Fiber Cladding Diameter	125μm
Fiber Coating Diameter	160μm~3000μm
Fiber Type	Single core fiber
Cleaved Length	5~16mm
Cleaved Angle	≤0.7°
Blade Life	48000 times
Operation Mode	Manual
Dimension	59mm(W)x55mm(D)x49mm(H)
Weight	257(g)
Package	X-50 fiber cleaver; collecting box; screw driver; user manual; carrying box

X-50D High Precision Fiber Cleaver



Features

- ※ Small and light, easy to carry
- ※ Blade life more than 48000 times
- ※ Support cleaved length 5~20mm
- ※ High quality materials, stable performance
- ※ High precision, specially designed for splicing work
- ※ Apply to 250μm/ 900μm fibers, tail optical fiber with 2-3mm in diameter, FTTH butterfly leather cable

Specifications

Fiber Cladding Diameter	125μm
Fiber Coating Diameter	160μm~3000μm
Fiber Type	Single core fiber
Cleaved Length	5~20mm
Cleaved Angle	≤0.7°
Blade Life	48000 times
Operation Mode	Semi-automatic
Dimension	58mm(W)x55mm(D)x54mm(H)
Weight	210(g)
Package	X-50D fiber cleaver; screw driver; user manual; carrying box